深圳市威睿晶科电子有限公司
Shenzhen Valueplus2 Electronic Co., Ltd

Model		J51LA
Product Size		125mm*77mm*45mm
Product Weight		178g/6.28oz
Shell color		Black, White
Laser Wavelength		905nm(Class 1 EN 60825, Eye safe)
Range Scope		6-699/1000/1500m
Ranging accuracy（m)		±1m @<400m; ＜±0.4%*D@>400m;
Ranging Resolution		0.1m
Angle Scope		-60°-60°
Angle measurement accuracy		±1°
Angle Display Resolution		0.1°
Jolt Technology		Have
Dispay Mode		Transmissive LCD display
Yard/Meter		Have
Telescope Magnification		6X
Field of view		7°
Object Diameter		22mm
Eyepiece Diameter		16mm
Exit Pupil Diameter		3.7mm
Exit Pupil Distance		19.7mm
Dipoter adjustment		-5D~+5D
Measurement Mode		Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode，Slope compensation
Protection Class		IP54
Certification		FCC,CE,ROHS
Working Temperature		-10°~50°
Battery type	2-99piece FOB 66USD	CR2-3V
Packaging Details	100-499piece FOB 59 USD	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG





深圳市威睿晶科电子有限公司
Shenzhen Valueplus2 Electronic Co., Ltd

Model		J51LB
Product Size		127mm*80mm*43mm
Product Weight		223g
Shell color		Green, White
Laser Wavelength		905nm(Class 1 EN 60825, Eye safe)
Range Scope		6-699/1000/1500/2000/3000m
Ranging accuracy（m)		±1m @<400m; ＜±0.4%*D@＞400m;
Ranging Resolution		0.1m
Angle Scope		-60°-60°
Angle measurement accuracy		±1°
Angle Display Resolution		0.1°
Jolt Technology		Have
Dispay Mode		Transmissive LCD display
Yard/Meter		Have
Telescope Magnification		6X
Field of view		7°
Object Diameter		22mm
Eyepiece Diameter		16mm
Exit Pupil Diameter		3.7mm
Exit Pupil Distance		19.7mm
Dipoter adjustment		-5D~+5D
Measurement Mode		Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode，Slope compensation
Protection Class		IP54
Certification		FCC,CE,ROHS
Working Temperature		-10°~50°
Battery type	2-99piece FOB 65USD	CR2-3V
Packaging Details	100-499piece FOB 59 USD	30Pcs/Carton Carton Size: 51*37*23cm G.W: 12KG





Model		J51LC
Product Size		116mm*75mm*37mm
Product Weight		142g
Shell color		Silvery, White,Golden
Laser Wavelength		905nm(Class 1 EN 60825, Eye safe)
Range Scope		6-699/1000/1500/2000/3000m
Ranging accuracy（m)		±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution		0.1m
Angle Scope		-60°-60°
Angle measurement accuracy		±1°
Angle Display Resolution		0.1°
Jolt Technology		Have
Dispay Mode		Transmissive LCD display
Yard/Meter		Have
Telescope Magnification		6X
Field of view		7°
Object Diameter		22mm
Eyepiece Diameter		16mm
Exit Pupil Diameter		3.7mm
Exit Pupil Distance		19.7mm
Dipoter adjustment		-5D~+5D
Measurement Mode		Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode， Slope compensation
Protection Class		IP54
Certification		FCC,CE,ROHS
Working Temperature		-10°~50°
Battery type	2-99piece FOB 59 USD	AAA *2 battery
Packaging Details	100-499piece FOB 49 USD	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG





Model	J51LD
Product Size	116mm*75mm*37mm
Product Weight	150g
Shell color	Black, Green, White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-699/1000/1500
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7°
Object Diameter	22mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode， Slope compensation
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	CR2-3V
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG



Model	J51LC
Product Size	120mm*78mm*40mm
Product Weight	164g
Shell color	White , Blue
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-699/1000/1500
Ranging accuracy (m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7°
Object Diameter	22mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode, Slope compensation
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	CR2-3V
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG

2-99piece
FOB 59 USD

100-499piece
FOB 50 USD





Model	J51LF
Product Size	118mm*78mm*40mm
Product Weight	168g/5.93oz
Shell color	Dark Green, White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-699/1000/1500/2000/3000m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7°
Object Diameter	22mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode， Slope compensation
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	Built in 3.7V/800mAh USB charging lithium battery
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG

2-99piece
FOB 56USD

100-499piece
FOB 49USD





Model	J51LG
Product Size	118mm*75mm*40mm
Product Weight	200g/7.05oz
Shell color	White , Greeen and white
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-699/1000/1500/2000/3000m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7°
Object Diameter	22mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Magnet	have
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode，Slope compensation
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	Built in 3.7V/800mAh USB charging lithium battery (type-c)
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 12KG





Model	J51KA
Product Size	113mm*80mm*43mm
Product Weight	159g
Shell color	Black, Royal Blue,White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	5-600/1000/1500m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7.5°
Object Diameter	24mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode, Slope compensation distance,
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	CR2-3V
Packaging Details 2-99piece FOB 49USD 100-499piece FOB 39USD	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG





Model	J51KB
Product Size	106mm*77mm*41mm
Product Weight	140g
Shell color	White，Blue, Black
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-600/1000/1500m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7.5°
Object Diameter	24mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Magnet	have
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode, Slope compensation distance,
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	CR2-3V
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG

2-99piece
FOB 49.9USD

100-499piece
FOB 45USD







Model	J51KC
Product Size	100mm*70mm*42mm
Product Weight	152g
Shell color	Black,White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	5-600/1000/1500m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7.5°
Object Diameter	24mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode, Slope compensation distance,
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	Built in 3.7V/800mAh USB charging lithium battery
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG

2-99piece
FOB 56USD

100-499piece
FOB 49USD







Model	J51SA
Product Size	89mm*73mm*37mm
Product Weight	145g/5.11oz
Shell color	Black, Cyan, White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	5-600/1000m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	6X
Field of view	7°
Object Diameter	21mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.3mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode 2-99piece FOB 65USD 100-499piece FOB 59 USD	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode, Slope compensation distance,
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	Built in 3.7V/800mAh USB charging lithium battery
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W: 11KG







Model	J51GA
Product Size	118mm*75mm*40mm
Product Weight	168g/5.93oz
Shell color	White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-600/1000/1500/2000/3000m
Ranging accuracy (m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	7X
Field of view	7°
Object Diameter	24mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode , Slope compensation distance ,
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	CR2-3V
Packaging Details	30Pcs/Carton Carton Size: 50*36*25cm G.W.: 11KG



Model	J51MA
Product Size	106mm*76mm*39mm
Product Weight	163g
Shell color	Slivery, White
Laser Wavelength	905nm(Class 1 EN 60825, Eye safe)
Range Scope	6-600/1000/1500/2000/3000m
Ranging accuracy（m)	±1m @<400m; <±0.4%*D@>400m;
Ranging Resolution	0.1m
Angle Scope	-60°-60°
Angle measurement accuracy	±1°
Angle Display Resolution	0.1°
Jolt Technology	Have
Dispay Mode	Transmissive LCD display
Yard/Meter	Have
Telescope Magnification	7X
Field of view	7°
Object Diameter	24mm
Eyepiece Diameter	16mm
Exit Pupil Diameter	3.7mm
Exit Pupil Distance	19.7mm
Dipoter adjustment	-5D~+5D
Measurement Mode	Distance measurement , height measurement , angle measurement , speed measurement , scanning measurement , Flagpole lock mode, Slope compensation distance,
Protection Class	IP54
Certification	FCC,CE,ROHS
Working Temperature	-10°~50°
Battery type	CR2-3V
Packaging Details	30Pcs/Carton Carton Size: 51*37*23cm G.W.: 11KG

2-99piece
FOB 70 USD

100-499piece
FOB 65 USD



