

ZX-29" Extreme



Frame : Carbon fiber, 29 " Dual Suspension MTB

Fork : Zoom 868AIR+RLO, Air Suspension, Remote Lockout, Through Axle

Handle Bars : Zoom MTB-AL-320BTFOV/ISO-M

Brakes : HD-M530, 4 Piston Hydr. disc brake (180/180), auto cut-off

Shift Levers : Shimano SL-M5100-R, Deore 11-Speed Rapidfire Plus

Rear Derailleur : Shimano RD-M5100, Deore 11-Speed

Front Hub : Joytech D041SB-B15。 Rear Hub : Joytech D442SB-S4S-B12

Cassette : Shimano Deore CS-M5100-11, 11-Speed 11-42T

Chain : Kmc E11 Sport/ EPT

Chainset : Bafang CW E1.11(11/128") 32T, CK C13.170 crank

Saddle : Justek TTS019

Seat Post : Zoom Alloy SP-C207/ISO-M

Battery : Bafang Lithium Ion 602WH 43V14Ah 3500mah Cell

Motor : Bafang Mid-Drive MM G522.250.C, 29" 43V 250Watt

Display : Bafang DP C190.CAN, 43V PA 0-5, 1 by default, 29", speed limit 25km/h

Controller : Bafang MM G522.250.C Groupset

ZX-27.5 AUrora Dual-SUS



**Max Assisted
Speed : 25km/h**

**Charging time :
9 hrs**

**Battery Distance :
125 KM**

Frame : Alu 27.5", integrated battery, custom tubing, internal routing

Fork : SRAM Recon 27.5" 100MM, through axle, Remote Lockout

Headset : FSA NO.69, semi-integrated, 1-1/8"/1.5"

Stem : Promax DA-2012(C)

Handle Bars : Promax HB-3188DB R18

Grips : VeloVLG-1745AD3

**Brakes : Shimano M6100, Hydraulic Disc Brake, 4 Pistons, Rotor
180/180**

Shift Levers : Shimano Deore SL-M5100, Papidfire-plus 11s

Rear Derailleur : Shimano Deore RD-M5100, SGS, Shadow plus 11s

**Hub : Kunteng KT-TWXF/ KT-M4TR 2 bearings, thru-axle KT-204B,
36H**

Chain : Kmc E11 TURBO-11

Chainset : Panasonic GX 38T Alloy crank

Pedals : Wellgo B249DU, Alloy

Saddle : S.R. MACH 2-A008URO, 264x140mm black

Seat Post : Promax SP-2059 alu

**Battery : Lithium Ion 900WH 36V25Ah Samsung E5 5000mah Cell,
5P10S 21700**

Motor : Panasonic GX Ultimate 36V 250Watt, 95N.m (Max)

**Display : Panasonic Side Color Display LCD 36V Eco/Std/Auto/High,
speed limit 25km/h**

Controller : Panasonic GX Ultimate groupset

ZX-29 Sentiero Dual-SUS



Max Assisted Speed : 25km/h

Charging time : 9 hrs

Battery Distance : 125 KM

Frame : Alu 29", integrated battery, custom tubing, internal routing
Fork : Suntour SF21-MOBIE-A32, 63mm, through axle, Mechanical Lockout
Headset : FSA NO.69
Stem : Integrated w/ Handlebars
Handle Bars : Mogubro M13 integrated w/LCD display
Grips : VeloVLG-1745AD3
Brakes : Shimano MT200, Hydraulic Disc Brake, 2 Pistons, Rotor 180/180
Shift Levers : Shimano Deore SL-M4100, Rapidfire-plus 10s
Rear Derailleur : Shimano Deore RD-M4120, SGS, Shadow 10s
Cassette : Shimano CS-M4100-10 10s 11/42

Chain : Kmc E10 TURBO-10
Chainset : Bafang CW G522.1B, 38T Alloy crank
Pedals : Wellgo B249DU, Alloy
Tyres : Maxxis M362P 29"X2.4"WT(M362P) 61-622 black tyre
Saddle : S.R. MACH 2-A008URO
Battery : Lithium Ion 900WH 36V25Ah Samsung E5 5000mah cell, 5P10S 21700
Motor : Bafang M510 36V 250Watt, 95N.m (Max)
Display : Mogubro M13 handlebar integrated display, LCD 36V PA 0-5, speed limit 25km/h
Controller : Bafang groupset

ZX-29 End Uro Trekking

**Max Assisted
Speed : 25km/h**

**Charging time :
4.8 hrs**

**Battery Distance :
100 KM**



Frame : Alu 29", integrated battery, custom tubing, internal routing

Fork : SRAM Recon 29" 100MM, through axle, Mechanical Lockout

Headset : FSA NO.69

Stem : Promax DA-2012(C)

Handle Bars : Promax HB-3188DB R18

Grips : VeloVLG-1745AD3

Brakes : Shimano M6100, Hydraulic Disc Brake, 4 Pistons, Rotor
180/180

Pedals : Wellgo B249DU, Alloy

Saddle : S.R. MACH 2-A008URO

Seat Post : Promax SP-2059 alu

Battery : Lithium Ion PowerPack 725WH 36V19.2Ah

Motor : Bosch Performance CX 36V 250Watt, 85N.m (Max)

Display : Purion LCD 36V Eco/Tour/Tour+*/Sport/eMTB**/Turbo,
speed limit 25km/h

Controller : Bosch Performance CX groupset

ZX-700C Voyager

**Max Assisted
Speed : 25km/h**

**Charging time :
7 hrs**

**Battery Distance :
100 KM**



Frame : Alu 700C, integrated battery, custom tubing, internal routing

Fork : Suntour SF21-XCM32-ATB-DS-RL-29, 100mm, Remote Lockout

Headset : FSA NO.69

Handle Bars : Promax HB-3188SP

Grips : VeloVLG-1777D2

Brakes : Shimano MT200, Hydraulic Disc Brake, 2 Pistons, Rotor
180/180

Shift Levers : Shimano Altus SL-M2010, Papidfire-plus 9s

Rear Derailleur : Shimano Altus RD-M370, SGS, 9s

Cassette : Shimano CS-HG400-9, 9s 12/36

Chain : Kmc E9 TURBO-9

Chainset : Bafang CW B1.11, 38T Alloy crank

Pedals : Wellgo M224G, Alloy

Tyres : Maxxis M2028 E50 E-BIKE 28"X2.0" (M2028EP) 49-622/ black
tyre

Saddle : S.R. FREEWAY-A094HRO

Battery : Lithium Ion 720WH 36V20Ah Chinese 5000mah cell, 4P10S
21700

Motor : Bafang M410 36V 250Watt, 80N.m (Max)

Display : Seekrun Q1 Stem integrated display, LCD 36V PA 0-5, speed
limit 25km/h

Controller : Bafang groupset

ZX-20" Cargo Life

Max Assisted
Speed : 32km/h

Charging time :
7 hrs

Battery Distance :
100 ~ 120 KM



Frame : Alu 20", Ext. battery (dual), custom tubing

Fork : ZX Power Alu 20" rigid fork, disc brake mount

Headset : FSA NO.69

Handle Bars : Zoom MTB-AL-332NBT-FOV

Grips : VeloVLG-1389D3(S)

Brakes : Shimano MT200, Hydraulic Disc Brake, 2 Pistons, Rotor
180/180

Shift Levers : Shimano Altus SL-M2010-7, 9s Rapidfire plus

Rear Derailleur : Shimano Altus RD-M370-L, 9s

Cassette : Shimano CS-HG400-9, 9s, 12-36(BH)

Chain : Kmc E9 Turbo

Pedals : Wellgo M224G Alloy

Tyres : Kenda K1032 ,20"X3.0" black tyre w/reflective sidewall

Saddle : S.R. HERTZ CITY-A092URO

Seat Post : Mogubro C5 alu, 27.2x400mm, integrated w/Taillight,
comply w/EN Std

Battery #1 : Lithium Ion 960WH 48V20Ah Samsung 5E 5000mah cell,
4P13S 21700

Battery #2 : Lithium Ion 672WH 48V14Ah Samsung 35E 3500mah cell,
4P13S 18650

Motor : Motinova MIGICT1 48V 500Watt, 100N.m (Max)

Display : Key-Disp KD986 LCD 48V PA 0-5, speed limit 32km/h

Controller : Motinova groupset

ZX-700C U Iti mate per lui

**Max Assisted
Speed : 32km/h**

**Charging time :
5 hrs**

**Battery Distance :
55 ~ 60 KM**



Frame : Alu 700C, integrated battery, custom tubing, internal routing

Fork : ZX Power Alu 700C rigid fork, disc brake mount

Headset : GineyeaT196, semi-integrated, 1-1/8"/1.5"

Stem : Key-Disp KD786-S integrated w/ display

Handle Bars : Zoom MTB-AL-320BTFOV/ISO-M

Grips : Velo VLG-1670AD3-L1, 130/130, comply w/PAHS Std

Brakes : Shimano MT200, Hydraulic Disc Brake, 2 Pistons, Rotor
160/160

Hub : Joytech D761DSE/ R: Shengyi Hub Motor

Cassette : Gates CDCRFW22, CDC CT1122WSE 22T

Chain : Gates CDN122 11M-125T-12CT BLACK CDN

Chainset : Gates CDXF555 55T BCD: 130mm Alloy crank

Pedals : Hengfeng HF-858, 9/16"100*86, Alu Ed black w/BS reflector

Tyres : Kenda K1068, 700C*45C black tyre

Battery : Lithium Ion 360WH 36V10Ah BAK 5000mah cell, 2P10S 21700

Motor : Shengyi Rear-Hub Motor DGWX2NDF 36V 350Watt, 48N.m
(Max)

Display : Key-Disp KD786-S integrated w/stem LCD 36V PA 0-5, speed
limit 32km/h

Controller : Lishui 36V14A

ZX-700C U Iti mate per lei

**Max Assisted
Speed : 25km/h**

**Charging time :
5 hrs**

**Battery Distance :
55 ~ 60 KM**



Frame : Alu 700C, integrated battery, custom tubing, internal routing

Fork : ZX Power Alu 700C rigid fork, disc brake mount

Headset : GineyeaT196, semi-integrated, 1-1/8"/1.5"

Stem : Key-Disp KD786-S integrated w/ display

Grips : Velo VLG-1670AD3-L1, 130/130, comply w/PAHS Std

**Brakes : Shimano MT200, Hydraulic Disc Brake, 2 Pistons, Rotor
160/160**

Tyres : Kenda K1068, 700C*45C black tyre

Battery : Lithium Ion 360WH 36V10Ah BAK 5000mah cell, 2P10S 21700

**Motor : Shengyi Rear-Hub Motor DGWX2NDF 36V 350Watt, 48N.m
(Max)**

**Display : Key-Disp KD786-S integrated w/stem LCD 36V PA 0-5, speed
limit 32km/h**

Controller : Lishui 36V14A

ZX-14 Tiny Q

Max Assisted
Speed : 25km/h

Charging time :
6 hrs

Battery Distance :
25 ~ 30 KM



Frame : Alu 14", integrated battery, custom tubing

Fork : 14" Steel Rigid fork

Headset : Xuhua XH-8067, semi-integrated, $18.5 \pm 1\text{mm}$, $1\frac{1}{8} \times 44 \times 30$

Stem : Yuqi SH-T840, bar bore 25.4mm, 395mm, comply w/EN Std

Handle Bars : Ruian CD-S101, 6° , 500mm, comply w/EN Std

Grips : HYH FAX-ZB10, 130/90, comply w/PAHS Std

Brakes : Logan LB-DX2016, disc brake, Rotor 160/160

Hub : Wanjia Integrated F/R wheel

Rims : Integrated w/Wanjia F/R wheels

Tyres : CST C-3007 14"*2.125 black tyre

Saddle : Hengli TH-XD236, black, Ergonomic, comply w/RoHs Std

Seat Post : Tengyue AG-01 steel, 27.2×300 , comply w/EN Std

Battery : Lithium Ion 280.8WH 36V7.8Ah EVE 2600mah cell, 3P10S 18650

Motor : Wanjia 14" Integrated Motor Wheel 36V 250Watt

Display : Yuwei YW-ZX-X6A LCD 36V PA 0-3, speed limit 25km/h

Controller : Yuwei 36V $14 \pm 1\text{A}$

Throttle : HYH FAX-ZB10 right-hand twist throttle

ZX-16 Nimbler

**Max Assisted
Speed : 32km/h**

**Charging time :
6 hrs**

**Battery Distance :
40 ~ 45 KM**



Frame : Alu 16", integrated battery, Liquid die forging technology, internal routing

Fork : 16" Alu Rigid fork

Headset : Neco H185, semi-integrated, $11.7 \pm 1\text{mm}$, $28.6 \times 44 \times 30$

Stem : Fuhou FH05W+FH10, bar bore 25.4mm, folding stem, comply w/EN Std

Handle Bars : RuianCD-S101, 6° , 500mm, comply w/EN Std

Grips : HYH FAX-ZB10, 130/90mm, comply w/PAHS Std

Brakes : JAK JAK-5, disc brake, Rotor 160/160

Hub : Jiabo Integrated F/R wheel

Chain : KMC S1RB

Chainset : SWHY A109-P2P, 46T Alloy crank

Tyres : CST C-3007 16"*2.125 black tyre

Saddle : Justek TTZ-065, black, Ergonomic, comply w/RoHs Std

Seat Post : Junyao JY-301 Alu 27.2*300, comply w/EN Std

Battery : Lithium Ion 417.6WH 36V11.6Ah 2900mah cell, 4P10S 18650

Motor : Jaobo 16" Integrated Motor Wheel 36V 350Watt

Display : Yonlin 61F-C LCD 36V PA 0-3, speed limit 32km/h

Controller : Santroll ZXDL-79 36V*12A

Throttle : HYH FAX-ZB10 right-hand twist throttle

Light : F: Wuxing QD252 connected w/lithium ion battery

ZX-20 Super Hawk Per lei

Max Assisted
Speed : 45km/h

Charging time :
5 hrs

Battery Distance :
60 ~ 65 KM



Frame : Alu 20", custom tubing, internal routing

Fork : Yishuo STRONG-20DH, Alu

Handle Bars : Ruian MD-S317 rise 18mm, 15° , 680mm, comply w/EN Std

Grips : Justek J174L/S, 110*75mm, comply w/PAHS Std

Brakes : Logan E500 Hydraulic Disc Brake, w/auto cut-off function, Rotor 180/180

Shift Levers : Shimano Altus SL-M315-8R, 8s Rapidfire plus

Rear Derailleur : Shimano Altus RD-M310-L, 8s

Hub : Joytech D101DSE / R: Bafang Rear-Hub Motor

Cassette : Shimano CS-HG31, 8s, 11-34T

Chain : Kmc F8 Turbo-8

Chainset : Prowheel PRO-V42PP-2, 42T Alloy crank

Pedals : Wellgo M224G, Alu

Tyres : Kenda K1188E 20"4.0(406-98) black tyre

Saddle : Huiye LL-I-500mm black, Ergonomic, comply w/RoHs Std

Battery : Lithium Ion 960WH 48V20Ah Samsung 5E 5000mah cell, 4P13S 21700

Motor : Bafang H550 Rear-Hub Motor 48V 750Watt, 80N.m (Max)

Display : Key-Disp KD86 LCD 48V PA 0-5, speed limit 45km/h

Controller : Lishui 36V23A

Throttle: Wuxing 76X.R.T+HT375, right-hand twist throttle